



SWE008

PN: SW19038EB56



Sunnyway Technology

Add: Building 65-302, No.421 Hongcao Road, Xuhui District, Shanghai
Tel: +86-021-6484 2326 Fax: +86-021-6484 2328
Email: sales@sunny-way.com Web: www.sunny-way.com



1. Electrical Specifications

Standards	WiFi 2.4GHz&BT
Frequency range (MHz)	2400-2500MHz
Peak Gain (dBi)	3.0~4.5dBi
Average Gain (dB)	-3.0~-2.0dB
VSWR	<2.0
Return Loss	<-9.5
Efficiency (%)	50~63%
Polarization mode	Linear
Radiation pattern	Omni-Directional
Output impedance (Ω)	50
Max. Input Power(W)	25


2. Mechanical and Environmental Specification

Mounting Type	Connector Mount
Connector Type	SMA
Antenna size(mm)	109mm* ϕ 10mm
Material	ABS
Operating Temperature (°C)	- 40 °C ~ + 85 °C
Storage Temperature(°C)	- 40 °C ~ + 85 °C




3. Antenna parameters


FRE (MHz)	2400	2450	2500
VSWR	1.98	1.90	1.91
Return Loss	-9.62	-10.12	-10.08
Eff (%)	60.2	61.6	56.3
Average Gain(dB)	-2.2	-2.1	-2.4




VSWR




Return Loss






Directional pattern


2400.000MHz



2450.000MHz




2500.000MHz





4. Antenna Drawings



4	SMA	SMA-J	black	1
3	Lower Firmware	ABS	black	1
2	Upper firmware	ABS	black	1
1	noumenon	ABS	black	1
Series	Component name	Specification	Color	Quantity